

EVERY INSTALL SHOULD BE THIS SMOOTH



**Whittemore**  
COMPANY, INC.

American Manufacturing since 1919

# E-Z Mix Pool Base

## Premium Vermiculite with Cement

Pre-Mixed Vermiculite and Cement for a smooth, liner-safe base

**SAME TRUSTED PERFORMANCE.  
EVEN FASTER INSTALLS.  
JUST ADD WATER.**



**PRE-MIXED, JUST  
ADD WATER**

**LINER FRIENDLY**

**GROUND WATER AND  
CRACK RESISTANT**

**THIRD GENERATION  
FAMILY OWNED  
COMPANY**

When time matters and consistency counts, Whittemore's Pre-Mix delivers.

We took our trusted vermiculite pool base and pre-blended it with portland cement, so all you do is add water and pour.

Engineered for smooth troweling, reliable results, and fewer delays. The result? A smooth, cushioned base that protects the liner, resists moisture, and trowels clean every time.



Backed by experience.  
Tested for performance.  
Trusted by contractors for 30+ years.



Contact us for bulk pricing or to place an order. [www.whittemoreco.com](http://www.whittemoreco.com) 978.681.8833



## E-Z Mix, Mixing Instructions

1. Place approximately eight (8) to ten (10) gallons of clean water into a paddle-type mixer.
2. Add two (2) bags of E-Z MIX while slowly rotating the paddles. Continue mixing for approximately 10-15 seconds or until all materials are completely mixed. Be certain not to overmix. Too much mixing can break down vermiculite particles and decrease the yield.
3. Stop mixing, take a sample, and add water if needed to achieve the desired consistency, based on weather, soil conditions, or the desired slope.
4. If water is added, rotate the paddles briefly again until the mix is well blended.
5. Bucket or wheel to point of application and trowel smooth.
6. Always make a trial batch to be certain the water added is correct for application. The recommended thickness in most vinyl in-ground pool bottoms is 2 inches. Consult the pool manufacturer to determine what thickness should be used with your particular pool.

**NEVER USE E-Z MIX WITHOUT COMPLETELY FOLLOWING INSTRUCTIONS.**



### Pool Base Coverage Chart

**BASED ON 2" THICKNESS**

<b>16' x 32'</b>	.....	<b>60-70 bags</b>
<b>18' x 36'</b>	.....	<b>75-80 bags</b>
<b>20' x 40'</b>	.....	<b>95-105 bags</b>

Pool Base Coverage chart figures are approximate and depend on job conditions.

Manufactured by:  
WHITTEMORE CO., INC.  
30 Glenn Street, Lawrence, MA 01843 Tel: (978) 681-8833

We hope the information provided here is helpful. It is based on data and knowledge considered to be true and accurate. It is offered for the user's consideration, investigation, and verification. Still, we do not warrant the results to be obtained. Please read all statements, recommendations, or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent or copyright.